

全方位門禁讀頭

多款門禁讀頭，提供全方位的運用



多輸出格式

AR-101-U/AR-725-K/AR-725-U/
AR-723-U/AR-331-K/AR-331-U/
AR-661U



雙頻

AR-101-U



體積小

AR-101-U/AR-723-U



觸碰式背光面板

AR-725-K/AR-725-U/
AR-331-K/AR-331-U



金屬材質機身

AR-331-K/AR-331-U



防塵/防水等級

IP55: AR-725-K/AR-725-U
IP56: AR-723-U/AR-725-U/
AR-331-K/AR-331-U/AR-661U



全方位門禁讀頭

多款門禁讀頭，提供全方位的運用

輕巧型
門禁讀頭
AR-101-U



長距離讀頭
AR-661U



輕巧型門禁讀頭
AR-723-U



按鍵型門禁讀頭
AR-721-K



感應頻率	13.56MHz	13.56MHz+125kHz	125kHz	125kHz	13.56MHz	125kHz	13.56MHz
工作電壓	9-24VDC		9-24VDC	9-24VDC		9-24VDC	
資料傳輸標準	EM Standard	ISO 14443/ISO 7816-4 Mifare Ultralight, Classic, DESFire EV1, NFC (card simulation)	EM Standard	EM Standard	ISO 14443/ISO 7816-4 Mifare Ultralight, Classic, DESFire EV1, NFC (card simulation)	EM Standard	ISO 14443/ISO 7816-4 Mifare Ultralight, Classic, DESFire EV1, NFC (card simulation)
感應距離	1-3cm	1-3cm	33-60cm	6-12cm	3-8cm	10-18cm	3-8cm
讀/寫功能	Read Only	Read/Write	Read Only	Read Only	Read/Write	Read Only	Read/Write
消耗功率	<1W		<3W	<1W		<1W	
通訊介面	RS-485 (9600 bps) / UART PORT (僅輸出) / 唯根24~34 / 唯根 Data 0 Data 1		Wiegand / 34+4, ASYNC	RS-485 (9600 bps) / UART PORT (僅輸出) / 唯根24~34 / 唯根 Data 0 Data 1		RS-485 (9600 bps) / UART PORT (僅輸出) / 唯根24~34 / 唯根 Data 0 Data 1	
傳輸速率	9600 bps(N,8,1)		9600 bps(N,8,1)	9600 bps(N,8,1)		9600 bps(N,8,1)	
環境溫度	-20 °C to +70 °C		-20 °C to +65 °C	-20 °C to +70 °C		-20 °C to +70 °C	
按鍵	No		No	No		Yes	
指示器	1組雙色LED+1組蜂鳴器		3 組LED & 1 組蜂鳴器	1組雙色LED+1組蜂鳴器		1組雙色LED+1組蜂鳴器	
防水指數	NO		IP56	IP56/ IP66(灌膠)		No	
外殼材質	ABS		ABS	ABS		ABS	
顏色	深灰		深灰	黑 / 灰 / 銀		深灰/銀	
外型尺寸(mm)	37(L)X37(W)X31(H)		228(L)X228(W)X38(H)	81(L)X43(W)X18(H)		111(L)X77(W)X26(H)	
重量(g)	30±10		1000±50	40±10		100±10	

窄型門禁讀頭
AR-331-U



窄型門禁讀頭
AR-331-K



門禁讀頭
AR-725-U



按鍵型門禁讀頭
(觸碰式背光)
AR-725-K



感應頻率	125kHz	13.56MHz	125kHz	13.56MHz	125kHz	13.56MHz	125kHz	13.56MHz
工作電壓	9-24VDC		9-24VDC		9-24VDC		9-24VDC	
資料傳輸標準	EM Standard	ISO 14443/ISO 7816-4 Mifare Ultralight, Classic, DESFire EV1, NFC (card simulation)	EM Standard	ISO 14443/ISO 7816-4 Mifare Ultralight, Classic, DESFire EV1, NFC (card simulation)	EM Standard	ISO 14443/ISO 7816-4 Mifare Ultralight, Classic, DESFire EV1, NFC (card simulation)	EM Standard	ISO 14443/ISO 7816-4 Mifare Ultralight, Classic, DESFire EV1, NFC (card simulation)
感應距離	3-7cm	1-3cm	3-7cm	1-3cm	5-15cm(725-U) 5-9cm(725-U*)	3-8cm(725-U) 3-5cm(725-U*)	5-15cm(725-K) 5-8cm(725-K*)	3-8cm(725-K) 3-5cm(725-K*)
讀/寫功能	Read Only	Read/Write	Read Only	Read/Write	Read Only	Read/Write	Read Only	Read/Write
消耗功率	<1W		<1W		<1W		<1W	
通訊介面	RS-485 (9600 bps) / UART PORT (僅輸出) / 唯根24~34 / 唯根 Data 0 Data 1		RS-485 (9600 bps) / UART PORT (僅輸出) / 唯根24~34 / 唯根 Data 0 Data 1		RS-485 (9600 bps) / UART PORT (僅輸出) / 唯根24~34 / 唯根 Data 0 Data 1		RS-485 (9600 bps) / UART PORT (僅輸出) / 唯根24~34 / 唯根 Data 0 Data 1	
傳輸速率	9600 bps(N,8,1)		9600 bps(N,8,1)		9600 bps(N,8,1)		9600 bps(N,8,1)	
環境溫度	-20 °C to +70 °C		-20 °C to +70 °C		-20 °C to +70 °C		-20 °C to +70 °C	
按鍵	No		*Illuminated Touch-panel		No		*Illuminated Touch-panel	
指示器	2組LED+1組蜂鳴器		2組LED+1組蜂鳴器		3組LED+1組蜂鳴器		1組雙色LED+1組蜂鳴器	
防水指數	IP56		IP56		IP55		IP55	
外殼材質	PC / 鋅合金		鋅合金		鋅合金+PC(725-U*) / PC(725-U)		鋅合金+PC(725-K*) / PC(725-K)	
顏色	Chrome		Chrome		黑 / 灰 / 銀 / 白		黑 / 灰 / 銀 / 白	
外型尺寸(mm)	158(H)X55(W)X30(D)		158(H)X55(W)X30(D)		79(L)X110(W)X26(H) (725-U) 125(L)X89(W)X30(H) (725-U*) 120±10(725-U) / 470±10(725-U*)		79(L)X110(W)X26(H) (725-K) 125(L)X89(W)X30(H) (725-K*) 120±10(725-K) / 470±10(725-K*)	
重量(g)	PC: 140±10 / 鋅合金: 245±10		PC: 140±10 / 鋅合金: 245±10					

產品架構

